



Grundpreis =
1 m Nutzlänge



Anschlagkette Edelstahl, geschweißte Ausführung, mit Schäkel Güteklasse 6

1-strängig			2-strängig			3-strängig			4-strängig		
Bestell-Nr.	Kette Ø		Bestell-Nr.	Kette Ø		Bestell-Nr.	Kette Ø		Bestell-Nr.	Kette Ø	
25000156	6		25000356	6		25000556	6		25000756	6	
25000158	8		25000358	8		25000558	8		25000758	8	
25000160	10		25000360	10		25000560	10		25000760	10	
25000163	13		25000363	13		25000563	13		25000763	13	
25000166	16	*	25000366	16	*	25000566	16	*	25000766	16	*
25000168	18	**	25000368	18	**	-	-		-	-	

* Ab 16 mm = GK 5

** Ab 18 mm in geschweißter Ausführung (auch 4, 5, 7 mm auf Anfrage)



Tragfähigkeiten / Auswahltablelle Güteklasse 6

Kette Ø						
	1-strängig		2-strängig		3+4-strängig	
	0°		0-45°	45-60°	0-45°	45-60°
[mm]	[t]		[t]	[t]	[t]	[t]
6	0,90		1,25	0,90	1,90	1,35
8	1,55		2,15	1,55	3,25	2,30
10	2,45		3,45	2,45	5,15	3,65
13	3,85		5,40	3,85	8,15	5,75
16 *	5,00		7,00	5,00	10,50	7,50
18 *	7,00		9,80	7,00	14,80	10,50
Faktor	1,0		1,4	1,0	2,1	1,5

* GK 5

NEUMANN GMBH
Hebesysteme Fördertechnik

Paul-Ehrlich-Straße 5a
63128 Dietzenbach

Tel. 06074 8504-0
Fax 06074 850412

E-Mail info@neumann-gmbh.com
www.neumann-gmbh.com