


Rundstahlkette DIN 766, GK2

verzinkt, geprüft, lehrenhaltig

Bestell-Nr.	Trag-fähigkeit [kg]	Abmessungen			Gewicht pro m [kg]
		d [mm]	t [mm]	b [mm]	
24020004	150	4	16	14,0	0,32
24020005	250	5	18	16,9	0,50
24020006	350	6	18	20,2	0,75
24020007	450	7	22	23,6	1,00
24020008	630	8	24	26,0	1,35
24020010	1000	10	28	34,0	2,25
24020013	1600	13	36	47,0	3,90
24020016	2500	16	45	54,0	5,80
24020018	3150	18	50	60,0	7,30
24020020	4000	20	56	67,0	9,00
24020023	5000	23	64	77,0	12,0
24020026	6300	26	73	87,0	15,0
24020028	7500	28	78	94,0	17,5
24020030	8500	30	84	101,0	20,0



Verkaufseinheit 30 m (ab 18 mm 20 m).

NEUMANN GMBH
Hebesysteme Fördertechnik

Paul-Ehrlich-Straße 5a
63128 Dietzenbach

Tel. 06074 8504-0
Fax 06074 850412

E-Mail info@neumann-gmbh.com
www.neumann-gmbh.com