



Grundpreis für
1 m Nutzlänge.



Edelstahl-Anschlagseil mit Sicherheitshaken und Edelstahlverpressung

1-strängig	
Bestell-Nr.	Seil-Ø
25160308	8
25160310	10
25160312	12
25160314	14
25160316	16
25160318	18
25160320	20
25160322	22

2-strängig	
Bestell-Nr.	Seil-Ø
25160358	8
25160360	10
25160362	12
25160364	14
25160366	16
25160368	18
25160370	20
25160372	22

3-strängig	
Bestell-Nr.	Seil-Ø
25160408	8
25160410	10
25160412	12
25160414	14
25160416	16
25160418	18
25160420	20
25160422	22

4-strängig	
Bestell-Nr.	Seil-Ø
25160458	8
25160460	10
25160462	12
25160464	14
25160466	16
25160468	18
25160470	20
25160472	22



Seil-Ø	1-strängig		2-strängig		2-strängig		3+4-strängig		endlos
	direkt	geschnürt	direkt		geschnürt		direkt		geschnürt
Faktor:	1	0,8	0-45° 1,4	45-60° 1	0-45° 1,12	45-60° 0,8	0-45° 2,1	45-60° 1,5	einfach 1,6
	t	t	t	t	t	t	t	t	t
8	0,60	0,50	0,80	0,60	0,70	0,48	1,25	0,90	1,00
10	1,00	0,80	1,40	1,00	1,10	0,80	2,10	1,50	1,60
12	1,30	1,00	1,80	1,30	1,45	1,00	2,70	1,95	2,10
14	1,80	1,45	2,50	1,80	2,00	1,45	3,80	2,70	2,90
16	2,30	1,80	3,20	2,30	2,60	1,80	4,80	3,45	3,70
20	3,60	2,90	5,00	3,60	4,00	2,90	7,60	5,40	5,80

NEUMANN GMBH
Hebesysteme Fördertechnik

Paul-Ehrlich-Straße 5a
63128 Dietzenbach

Tel. 06074 8504-0
Fax 06074 850412

E-Mail info@neumann-gmbh.com
www.neumann-gmbh.com