



Hochfeste Schäkel mit Bolzen, Mutter und Splint Gerader Form, verzinkt

Bestell-Nr.	Trag-fähigkeit	Nenn-größe	Abmessungen						Gewicht ca.
			d1	d2	d3	d4	b1	h1	
	[t]	NG	[mm]	[mm]	[mm]	Zoll *	[mm]	[mm]	[kg]
29020050	0,50	1/4	6	8	17	1/4	12	22	0,06
29020051	0,75	5/16	8	10	21	5/16	13	26	0,10
29020052	1,00	3/8	10	12	26	3/8	16	31	0,15
29020053	1,50	7/16	11	14	28	7/16	18	36	0,22
29020054	2,00	1/2	13	16	30	5/8	21	41	0,34
29020055	3,25	5/8	16	19	40	3/4	27	51	0,70
29020056	4,75	3/4	19	22	48	7/8	32	60	1,18
29020057	6,50	7/8	22	25	54	1	36	71	1,64
29020058	8,50	1	25	29	60	1 1/8	43	81	2,41
29020059	9,50	1 1/8	29	32	67	1 1/4	46	90	3,27
29020060	12,00	1 1/4	32	35	76	1 3/8	52	100	4,59
29020061	13,50	1 3/8	35	38	84	1 1/2	57	113	6,00
29020062	17,00	1 1/2	38	41	92	1 5/8	60	124	8,33
29020063	25,00	1 3/4	44	51	110	2	73	146	12,83
29020064	35,00	2	51	57	127	2 1/4	83	171	18,50
29020065	55,00	2 1/2	63	70	152	2 2/3	105	203	38,03
29020066	85,00	3	76	82	165	3 1/4	127	216	55,35
29020067	120,00	3 1/2	89	95	203	3 3/4	146	267	98,10
29020068	150,00	4	102	108	229	4 1/4	165	305	139,50

* Gewinde



NEUMANN GMBH
Hebesysteme Fördertechnik

Paul-Ehrlich-Straße 5a
63128 Dietzenbach

Tel. 06074 8504-0
Fax 06074 850412

E-Mail info@neumann-gmbh.com
www.neumann-gmbh.com