



Gabelseilhülse früher DIN 83313 Form C

komplett mit Bolzen, Mutter und Splint

Bestell-Nr.	Nenngröße	Seil-Ø [mm]	Tragfähigkeit [t]	Abmessungen								Gewicht ca. [kg]
				b ₁ [mm]	b ₂ [mm]	c [mm]	d ₁ [mm]	d ₃	d ₄ [mm]	e [mm]	h [mm]	
22462050	1,6	12-14	1,60	37	27	12	17	M 20	20	55	147	1,10
22462051	2,5	14-18	2,50	45	33	14	20	M 24	24	67	175	1,80
22462052	3	16-20	3,15	50	38	16	22	M 27	27	73	195	2,40
22462053	4	18-22	4,00	54	42	18	24	M 30	30	81	212	3,20
22462054	5	20-24	5,00	60	47	20	27	M 36	36	88	237	5,00
22462055	6	22-28	6,30	67	53	23	30	M 39	39	94	262	6,70
22462056	8	26-30	8,00	73	60	26	33	M 45	45	104	289	9,50
22462057	10	26-34	10,00	80	66	29	36	M 48	48	116	320	13,00
22462058	12	32-38	12,50	89	73	32	40	M 52	52	130	356	17,00
22462059	16	36-44	16,00	100	81	35	45	M 60	60	143	397	24,00
22462060	20	40-50	20,00	110	90	40	50	M 68	68	157	435	31,00
22462061	25	44-54	25,00	120	100	43	55	M 72x6	72	179	480	41,00
22462062	32	50-62	31,50	132	110	48	60	M 80x6	80	191	525	55,00
22462063	40	58-72	40,00	150	125	54	68	M 90x6	90	218	595	80,00
22462064	50	62-76	50,00	165	140	60	75	M 100x6	100	238	655	105,00



Weiterhin lieferbar in Ausführung roh, ohne Bolzen, Bohrung unbearbeitet (Rohmaß)

NEUMANN GMBH
Hebesysteme Fördertechnik

Paul-Ehrlich-Straße 5a
63128 Dietzenbach

Tel. 06074 8504-0
Fax 06074 850412

E-Mail info@neumann-gmbh.com
www.neumann-gmbh.com